

(14/NRL-MR-4308

	SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)		
	(9) REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM	
	NRL Memorandum Report, 308 2. GOVT ACCESSION NO.		
٤	4. TATLE (and SUBTILIS)	5. TYPE OF REPORT & PERIOD COVERED	
	HEATING AT THE ELECTRON CYCLOTRON FREQUENCY IN THE ISX-B TOKAMAK	Interim report on a continuing NRL problem	
1		6. PERFORMING ORG. REPORT NUMBER	
	B. Hui V.L. Granatstein, R.R. Chu, A.C. England, C.M. Loring, U.C.	. CONTRACT OR GRANT NUMBER(a)	
	Eldridge**, H.C. Howe‡, A.G. Kulchar**, E. Lazarus‡, M. Murakami‡, and J.B. Wilgen‡		
	9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS	
	Naval Research Laboratory Washington, D.C. 20375	NRL Problem 67-0865-0-0 DOE EX-77-A-34-1#15	
	11. CONTROLLING OFFICE NAME AND ADDRESS	August 14 180	
	Department of Energy Washington, D.C. 20585	Augus 14, 1980	
	14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office)	17 15. SECURITY CLASS. (of this report)	
	(12)	UNCLASSIFIED	
		15e. DECLASSIFICATION/DOWNGRADING SCHEDULE	
	16. DISTRIBUTION STATEMENT (of this Report)		
Approved for public release; distribution unlimited.			
ı	17. DISTRIBUTION STATEMENT (of the ebetrect entered in Block 20, if different from Report)		
	•		
*JAYCOR, Alexandria, VA 22304 †MIT, Cambridge, MA 02139 **Univ. of Tennessee, Knoxville, TN 38163 ‡Oak Ridge National Laboratory, Oak Ridge, TN 37831			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)		D	
Electron Cyclotron Heating (ECH) Gyrotron			
Tokamak Plasma Heating			
20. ABSTRACT (Continue on reverse side if necessary and identify by black number)			
	We report results of electron cyclotron heating (ECH) experiments in which 80-kW of microwave power from a 35-GHz gyrotron is injected into tokamak with large single pass absorption. For 10-ms microwave pulses, incident from the high field side of the torus, the central electron temperature increases from 850 eV to 1250 eV, in agreement with empirical transport code calculations. For the first time in a tokamak, we demonstrate that electron temperature scales linearly with ECH power.		
	•		

# HEATING AT THE ELECTRON CYCLOTRON FREQUENCY IN THE ISX-B TOKAMAK

Plasma heating by microwaves at the electron cyclotron resonance frequency has been demonstrated to be an effective technique in a variety of confinement devices.  $^{1-3}$  The recent development of the gyrotron  $^4$  as a high power, short wavelength microwave source has made it possible to perform electron cyclotron heating experiments in tokamaks. Numerous advantages are evident in this method of heating tokamak plasma. As depicted in Fig. 1, the microwave energy can be deposited in a thin resonant layer which exists at the major radius (R) where the electron cyclotron frequency ( $f_c$ ) is equal to the microwave source frequency ( $f_g$ ). The microwave absorption coefficient increases with electron temperature  $f_c$ , making this an attractive scheme for supplemental heating. The wave damping mechanism is linear and heats the bulk of the electrons, rather than producing a high energy tail. Antenna structures are small compared with those required for heating at the ion cyclotron or lower hybrid frequencies, since ECH wavelengths are less than 1 cm for most tokamaks.

There exist several theories  $^{7-11}$  of ECH in tokamaks which predict that the extraordinary wave is more heavily damped than the ordinary wave at oblique incidence from the high field side. For the parameters of the ISX-B tokamak (major radius  $R_0 = 93$  cm, minor radius a = 27 cm,  $T_e = 1$  keV), theory  $^7$  predicts 100% single pass absorption of the extraordinary wave, while

DISTRIBUTION/AVAILABILITY CODES
Dist. AVAILL and/or SPECIAL

Manuscript submitted May 30, 1980

the ordinary wave can undergo about 50% single pass absorption, depending upon the angle of incidence and the electron density.

Previous experiments by Alikaev et al.  $^5$  used short (750  $\mu$ s) microwave pulses at power levels of less than 60 kW to perform bulk heating in the TM-3 tokamak ( $R_0$  = 40 cm, a = 8 cm). The energy confinement time,  $\tau_E$ , in this device was about 300  $\mu$ s with a plasma current of 60 kA. Because of the small plasma volume and low electron temperature (400 eV) in TM-3, significant single pass absorption could not occur.  $^7$  Since the unpolarized microwaves were launched from the low field side of the tokamak, the extraordinary wave component encountered a cutoff and could not propagate directly to the cyclotron resonance.

Here we present the results of ECH experiments in which the larger size of the tokamak and higher electron temperature ( $\sim$ 1 keV) assure high single pass microwave absorption. The energy confinement time ( $\tau_E$  = 10-15 ms) and ohmic heating power (100-150 kW) in ISX-B are roughly comparable to the NRL gyrotron<sup>12</sup> pulse length (10-20 ms) and output power (100-140 kW). Thus, these experiments provide a significant scaling of the previous ECH research.

The NRL gyrotron oscillator operated at a frequency ( $f_g = 35.08 \text{ GHz}$ ) which corresponds to a resonant field of 12.5 kG with cutoff densities of 1.5 x  $10^{-13}$  cm<sup>-3</sup> for the ordinary wave and 3 x  $10^{13}$  cm<sup>-3</sup> for the extraordinary wave. Microwave output was in the TE<sub>01</sub> circular mode, which was transmitted to the tokamak with overmoded copper waveguide (6 cm i.d.). Transmission losses between the gyrotron and the tokamak were about 1 dB. As shown in Fig. 1, the microwave power was launched into the plasma from the midplane of the high field side of the tokamak, eliminating the cutoff of the extraordinary wave that occurs on the low field side. The incident angle

was set at  $45^{\circ}$  from a major radius at the plasma edge. Ray tracing calculations in toroidal geometry predict that this angle of incidence results in almost 100% single pass absorption of the extraordinary wave and less than 50% single pass absorption of the ordinary wave. Since the radiated power was an equal mixture of ordinary and extraordinary waves one expects a single pass heating efficiency of less than 75%. Of the radiation which is not absorbed in a single pass only a small fraction is reflected directly back to the center of the plasma because of both the extraordinary wave cutoff and the divergence of the microwave beam  $(+17^{\circ})$ .

Several electron temperature diagnostics were located about  $180^{\circ}$  around the torus from the antenna. A laser Thomson scattering system had the capability of 4 pulses per tokamak shot with pulse separations as small as 1 ms, enabling the time evolution of  $T_e$  to be measured during the heating pulse. Detection of the black-body emission at the second cyclotron harmonic provided a continuous measurement of the electron temperature. This diagnostic utilized a standard superheterodyne receiver, with a local oscillator frequency of 70.5 GHz, and I.F. amplifier with 60 MHz bandwidth. Detuning the local oscillator from the second harmonic of the gyrotron frequency eliminated the enhanced second harmonic generation that was observed at exactly 2  $f_g$ . A similar superheterodyne receiver with a local oscillator frequency of 58 GHz measured the electron temperature at a major radius R = 112 cm, as illustrated by the region in Fig. 1 where  $f_c = 29$  GHz.

A comparison is given in Figs. 2(a) and 2(b) of the electron temperature and density profiles before and after electron cyclotron resonance heating. These results were obtained with  $\sim 80$  kW of microwave power applied for 10 ms, with the resonant magnetic field located at the center of the plasma.

Peak electron density was slightly above the cutoff density for the ordinary wave but below the extraordinary wave cutoff density. The central electron temperature increased from 850 eV to 1250 eV, becoming more peaked at the center, as expected. This temperature increase is verified by the increase in the second harmonic cyclotron emission. Assuming 100% microwave absorption with a gaussian energy deposition profile centered at the resonant surface, a transport code predicts this temperature increase for an empirical electron heat conduction coefficient that is independent of  $T_{\rho}$ . For a microwave input power of 80 kW the heating efficiency is estimated to be about 60% from a power balance equation that includes: (i) the change in plasma electron energy (from 766 J to 850 J) divided by the ECH pulse length (10 ms), (ii) the decrease in ohmic heating power (30 kW), and (iii) the change in electron energy divided by the electron energy confinement time (9.1 ms). During the microwave pulse, the central electron density is seen to decrease by about 15%. This large density decrease was usually observed during the microwave pulse in these experiments. No hard x-rays were generated by the ECH, and the soft x-ray spectrum did not exhibit a high energy tail, confirming that the bulk of the electrons were heated.

The temporal evolution of the electron density, loop voltage, and central electron temperature are shown in Fig. 3(a) for 80 kW microwave injection with 16 ms ECH pulse duration. Electron temperature at the center of the plasma [Fig. 3(b)] increased from 850 eV to approximately 1300 eV with fairly close agreement between the Thomson scattering and second cyclotron harmonic detection (SHD) diagnostics. An empirical transport code yields a temperature rise and decay that closely resembles the SHD diagnostic.

Loop voltage decreased during the ECH pulse from approximately 1.1 V to 0.66 V, which, from the Spitzer resistivity, indicates an electron temperature increase of about 40%. Both the horizontal and vertical line-average densities decreased by approximately 15% during the heating pulse. A density decrease has also been observed in neutral beam heated plasmas in ISX-B. The experimental density decrease is anomalously large with ECH, since empirical transport code calculations predict only a 2% decrease in line-average density. This explains why the experimental SHD electron temperatures are slightly higher than the theoretical values in Fig. 3(b).

In order to determine whether the electron cyclotron heating is linear, the gyrotron power was varied. These results, shown in Fig. 4, indicate a linear dependence of  $T_{\rm e}$  on microwave power with a heating rate of  $\sim 6$  eV per kilowatt. The agreement between the Thomson scattering data and the second cyclotron harmonic detection data is evidence—that nonthermal electrons are not produced by ECH. This is the first time that a linear heating rate has been demonstrated for heating at the electron cyclotron frequency in a tokamak.

No ion heating was observed in these ECH experiments. One does not expect ion heating since the low plasma density provides weak coupling between electrons and ions; the microwave pulse lengths (10-16 ms) and energy confinement time (10 ms) are much shorter than the electron-ion equilibration time (~50 ms). However, as tokamaks are scaled toward reactor parameters and gyrotrons with higher frequencies and longer pulses are developed, significant ion heating could occur. Results of the present experiments indicate that ECH may prove to be an important supplementary technique for heating CTR plasmas toward ignition temperature.

We gratefully acknowledge the support of J. Sheffield and the entire ISX-B tokamak group, especially M. J. Saltmarsh, H. E. Ketterer, S. C. Bates, C. E. Bush, J. L. Dunlap, R. Dyer, R.Isler, T.C. Jernigan, G. H. Neilson, and V. K. Pare'. We also thank W. M. Manheimer and E. Ott for useful discussions.

This work was supported by the Office of Fusion Energy, U.S. Department of Energy under the following contracts: (i) Contract No. EX-77-A-34-1015 with the Naval Research Laboratory; (ii) Contract No. W-7405-ENG-26 with the Union Carbide Corporation; (iii) Contract No. ET-78-S-02-4714 with the Massachusetts Institute of Technology.

## **REFERENCES**

- 1. J. C. Sprott, Phys. Fluids 14, 1795 (1971).
- 2. M. Okabayashi, K. Chen, and M. Porkolab, Phys. Rev. Lett. <u>31</u>, 1113 (1973).
- C. L. Hedrick, et al., in Plasma Physics and Controlled Nuclear
  Fusion Research (International Atomic Energy Agency, Vienna, 1977),
  Vol. 2, p. 145.
- V. A. Flyagin, et al., IEEE Trans. Microwave Theory Tech. 25, 514
   (1977); J. L. Hirschfield and V. L. Granatstein, IEEE Trans. Microwave
   Theory Tech. 25, 522 (1977).
- V. V. Alikaev, et al., Fiz. Plasmy 2, 390 (1976) (Sov. J. Plasma Phys. 2, 212 (1976)).
- 6. P. C. Efthimion, et al., Bull. Am. Phys. Soc. 24, 991 (1979).
- 7. E. Ott, B. Hui, and K. R. Chu, Phys. Fluids (to be published).
- 8. T. M. Antonsen and W. M. Manheimer, Phys. Fluids <u>21</u>, 2295 (1978).
- 9. O. Eldridge, Phys. Fluids <u>15</u>, 676 (1972).
- I. Fidone, et al., Phys. Fluids 21, 645 (1978).
- 11. A. G. Litvak, et al., Nucl. Fusion 17, 659 (1977).
- M. E. Read, et al., Technical Digest of 1979 International Electron Devices Meeting, p. 172, IEEE Publications, Piscataway, N. J.




Fig. 1 — Experimental configuration. The electron cyclotron frequency ( $f_c$ ) is shown for a toroidal magnetic field ( $B_T$ ) of 12.5 kG on axis. The ECH resonant surface ( $f_c$  = 35 GHz) is located at the center of the plasma.




Fig. 2 — Electron temperature profile (a) and density profile (b) measured by Thomson scattering. Dashed lines denote data taken before ECH (118 ms into tokamak shot); solid lines represent data at the end of ECH (at 130 ms). Data is for 80-kW microwave injection with a 10-ms ECH pulse starting at 120 ms. B<sub>T</sub> was 12.5 kG, line-average electron density ( $\overline{n}_e$ ) was  $\sim 10^{13}$  cm<sup>-3</sup>, and plasma current (Ip) was 83 kA.




Fig. 3 — (a) Central electron temperature (from second harmonic cyclotron emission), loop voltage (V $\varrho$ ), and line-average electron density vs time for 80-kW microwave pulse of 16-ms duration. (b) Electron temperature measurements from second cyclotron harmonic detection are indicated by a solid line, Thomson scattering measurements by circles, and electron temperature calculated from empirical transport code is shown by dashed line. Plasma parameters were:  $B_T\cong 12.5~kG, \, \overline{n}_e\cong 10^{13}~cm^{-3}$ , and Ip = 115 kA.




Fig. 4 — Central electron temperature vs microwave power with 15 ms ECH pulse length. Electron temperature measured by Thomson scattering ( $\Phi$ ) and second harmonic cyclotron emission ( $\Delta$ ). Plasma parameters were: B<sub>T</sub>  $\cong$  12.5 kG,  $n_e$   $\cong$  10<sup>13</sup> cm<sup>-3</sup>, and Ip = 85 kA.

#### GYROTRON & ECH DISTRIBUTION LIST

## No. of Copies

#### Addressee

(25)Naval Research Laboratory

(26) Attn: Name/Code

4555 Overlook Avenue, S.W. Washington, D.C. 20375

Code: 4700 - Dr. T. Coffey

4740 - Dr. V.L. Granatstein

4740 - Dr. R.K. Parker 4740 - Dr. K.R. Chu 4740 - Dr. M.E. Read

4740 - Dr. C.W. Roberson 4740 - Dr. S. Gold

4790 - Dr. P.A. Sprangle

4790 - Dr. B. Hui

4790 - Dr. W.M. Manheimer 6850 - Dr. L.R. Whicker 6853 - Dr. A. Ganguly 6805 - Dr. S.Y. Ahn 6805 - N.R. Vanderplaats

6875 - Dr. R. Wagner

On-Site Contractors:

Code: 4740 - Dr. J.M. Baird (B-K Dynamics)

4740 - Dr. L. Barnett (B-K Dynamics)

4740 - Dr. D. Dialetis (SAI) 4740 - A.J. Dudas (JAYCOR)

4740 - Dr. R.M. Gilgenbach (JAYCOR)

4740 - Dr. K.J. Kim (JAYCOR) 4740 - Dr. Y.Y. Lau (SAI)

4740 - Dr. J.S. Silverstein (HDL)

4790 - Dr. A.J. Drobot SAI) 4790 - Dr. C.M. Hui (JAYCOR) 4790 - Dr. J. Vomvoridis (JAYCOR) 5704S - Dr. S. Smith (LOCUS, Inc.)

(3) Secretary Department of Energy Attn: Washington, D.C. 20545 Dr. P. Stone (G-234) Dr. M. Murphy (G-234) Dr. J. Willis (G-234)

(1) Air Force Avionics Laboratory Attn: W. Friz Wright/Patterson AFB, Ohio 45433

(1)Bell Laboratories Attn: Dr. W.M. Walsh, Jr. 600 Mountain Avenue Murray Hill, New Jersey 07971

## No. of Copies

#### Addressee

- (1) Columbia University
  Department of Electrical Engineering
  Attn: Dr. S.P. Schlesinger
  New York, New York 10027
- (1) Dartmouth College
  Physics Department
  Attn: Dr. John Walsh
  Dartmouth, New Hampshire 03755
- (12) Defense Technical Information Center Cameron Station 5010 Duke Street Alexandria, Virginia 22314
- (1) Georgia Institute of Technology
  Engineering Experimental Station
  Attn: Dr. James J. Gallagher
  Atlanta, Georgia 30332
- (3) Hughes Aircraft Co.
  Attn:
  Electron Dynamics Division
  3100 Lomita Boulevard
  Torrance, California 90509

Dr. J.J. Tancredi K. Arnold K. Amboss

- (1) Los Alamos Scientific Laboratory
  Attn: Dr. Paul Tallerico
  P.O. Box 1663
  Los Alamos, New Mexico 87545
- (1) Massachusetts Institute of Technology Research Laboratory of Electronics Attn: Dr. G. Bekefi Bldg. 36, Rm. 36-225 Cambridge, Massachusetts 02139
- (3) Massachusetts Institute of Technology
  Plasma Fusion Center
  Attn:
  167 Albany St., N.W. 16-200
  Cambridge, Massachusetts 02139

Dr. R. Davidson Dr. M. Porkolab Dr. R. Temkin

- (1) Northrop Corporation
  Defense System Department
  Electronics Division
  Attn: G. Doehler
  175 W. Oakton St.
  Des Plaines, Illinois 60018
- (2) Oak Ridge National Laboratories
  Attn:
  P.O. Box Y
  Oak Ridge, Tennessee 37830

Dr. A. England M. Loring

# No. of Copies

## Addressee

- (1) Princeton University
  Plasma Physics Laboratory
  Attn: Dr. H. Hsuan
  Princeton, New Jersey 08540
- (2) Raytheon Company
  Microwave Power Tube Division
  Attn:
  Willow St.
  Waltham, Massachusetts 02154
- (1) Science Applications, Inc.
  Attn: Dr. Alvin Trivelpiece
  1200 Prospect St.
  La Jolla, California 92037
- (1) Stanford University
  SLAC
  Attn: Dr. Jean Lebacqz
  Stanford, California 94305
- (1) University of Arizona
  Optical Sciences Center
  Attn: Dr. W.E. Lamb
  Tucson, Arizona 85720
- (1) Varian Associates
  Bldg. 1
  Attn: Dr. H. Jory
  611 Hansen Way
  Palo Alto, California 94303
- (1) Yale University
  Mason Laboratory
  Attn: Dr. J.L. Hirshfield
  400 Temple Street
  New Haven, Connecticut 06520
- (1) Kings College
  University of London
  Attn: Dr. P. Lindsay
  London, United Kingdom
- (1) Nagoya University
  Institute of Plasma Physics
  Attn: Dr. H. Ikegami
  Nagoya, Japan 464
- (1) National Taiwan University
  Department of Physics
  Attn: Dr. Yuin-Chi Hsu
  Taipei, Taiwan, China

R. Edwards R. Handy

# No. of Copies

## Addressee

- (1) TFR Group
  DPH PFC
  Attn: Dr. A. Cavallo
  92260 Fontenay-auix Roses
  France
- (1) Thompson
  C.S.F./DET/TDH
  Attn: Dr. G. Mourier
  2 Rue Latecoere
  78140 Velizy Villa conblay
  France
- (1) UKAEA Culham Laboratory
  Attn: Dr. A.C. Riviere
  Abingdon
  Oxfordshire
  United Kingdom